

Pedestals

Overview

Pedestal Range	Specification	Void Ranges	Clip in Stringer Compatible	Screw Down Stringer Compatible	
М	BS EN 12825	50mm - 185mm	As Standard	Upon Request	
E	BS EN 12825/ PSA MOB PF2 PS/SPU	50mm - 575mm	As Standard	As standard on H5E and above.	
н	PSA MOB PF2 PS/SPU	26mm - 675mm	As Standard	As standard on H5E and above.	
x	PSA MOB PF2 PS/SPU	75mm - 1525mm	As Standard	As Standard	

Pedestal Range	Base Size	Base Tube Size	Socket Head Size	90mm Top Disc Thickness	Locking Nut Thickness
М	85mm x 85mm x 1.5mm	16mm OD	22mm OD	3mm	3mm
E	85mm x 85mm x 1.5mm	20mm OD	25.4mm OD	3mm	3mm
н	100mm x 100mm x 2mm	25.4mm OD	31.75mm	3mm	3mm
Х	100mm x 100mm x 3mm	31.75mm OD	38.1mm	3mm	3mm



For more information get in touch with us at:

Tel: +44 (0)1384 637 777 | Web: www.isaacgrainger.co.uk

Fax: +44 (0)1384 637 111 | Email: sales@isaacgrainger.co.uk

ISAAC H. RAINGER'S

Traditional Engineers Supplying a Comprehensive Range of Access Flooring Products and Systems

Century Works, 8 Gawne Lane, Cradley Heath, West Midlands B64 5QY United Kingdom

FINISHING OPTIONS

Zinc plated and clear passivated as standard. **Astec 3000** and **Nickel** finishes are available on all products.



SPECIAL OPTIONS

Special **Ramp Head** and **Cantelever** options are available.





łead Cantelever